



Acetic Acid, 2.0N (2.0M)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 12/11/2013

Revision date: 10/13/2020

Supersedes: 09/06/2016

Version: 1.2

SECTION 1: Identification

1.1. Identification

Product form : Mixtures
 Product name : Acetic Acid, 2.0N (2.0M)
 Product code : LC10390

1.2. Recommended use and restrictions on use

Use of the substance/mixture : For laboratory and manufacturing use only.
 Recommended use : Laboratory chemicals
 Restrictions on use : Not for food, drug or household use

1.3. Supplier

LabChem, Inc.
 1010 Jackson's Pointe Ct.
 Zelienople, PA 16063 - USA
 T 412-826-5230 - F 724-473-0647
 info@labchem.com - www.labchem.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 or +1-703-741-5970

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture


GHS US classification

Skin corrosion/irritation Category 1C H314 Causes severe skin burns and eye damage
 Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage
 Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS US) :

P260 - Do not breathe mist, spray, vapors.
 P264 - Wash exposed skin thoroughly after handling.
 P280 - Wear eye protection, protective gloves.
 P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Acetic Acid, 2.0N (2.0M)

Safety Data Sheet

Acetic Acid, 2.0N (2.0M)

Safety Data Sheet

Acetic Acid, 2.0N (2.0M)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Other information : No supplementary information available.

Transport by sea

Transport document description (IMDG) : UN 2790 ACETIC ACID SOLUTION, 8, III

UN-No. (IMDG) : 2790

Proper Shipping Name (IMDG) : ACETIC ACID SOLUTION

Class (IMDG) : 8 - Corrosive substances

Packing group (IMDG) : III - substances presenting low danger

Limited quantities (IMDG) : 5 L

Air transport

Transport document description (IATA) : UN 2790 Acetic acid solution, 8, III

UN-No. (IATA) : 2790

Proper Shipping Name (IATA) : Acetic acid solution

Class (IATA) : 8 - C

