

respiratory medical device. Immediate medical attention is required.

Ingestion Do not induce vomiting. Call a physician or Poison Control Center immediately.

Most important symptoms/effects Breathing difficulties. Causes burns by all exposure routes. . Symptoms of overexposure

may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe

damage to the delicate tissue and danger of perforation

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool closed

containers exposed to fire with water spray.

Unsuitable Extinguishing Media No information available

Flash Point 79 °C / 174.2 °F Method - No information available

Autoignition Temperature

Explosion Limits

605 °C / 1121 °F

Upper 8.6 vol % **Lower** 1.7 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Combustible material. Risk of ignition. Containers may explode when heated.

Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO2

8. Exposure controls / personal protection

Exposure Guidelines

9. Physical and chemical properties

Physical State Appearance Odor Odor Threshold pH Melting Point/Range Solid Colorless sweet No information available 4-5 @ 20°C 10 g/L aq.sol 39

Molecular Weight 94.11

10. Stability and reactivity

Reactive Hazard Yes

Stability Hygroscopic, Light sensitive.

Conditions to Avoid Avoid dust formation. Incompatible products. Exposure to moisture. Exposure to light. Keep

away from open flames, hot surfaces and sources of ignition.

Incompatible Materials

polymer made with any free-radical initiator regardless of the amount used.

- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.
- XU Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
- Y1 Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
- Y2 Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b)

Not applicable

SARA 313

	Component	CAS-No	Weight %	SARA 313 - Threshold Values %
	Phenol	108-95-2	>95	1.0
Acute Health Chronic Healt Fire Hazard Sudden Relea	h Hazard se of Pressure Hazard	Yes Yes Yes No		
Reactive Haza	ard	Yes		

Clean Water Act

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Phenol	X	1000 lb	X	X

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Phenol	X		-

OSHA Occupational Safety and Health Administration Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component

Mexico - Grade No information available

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class B3 Combustible liquid

D1A Very toxic materials E Corrosive material D2A Very toxic materials



16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 03-Dec-2010

 Revision Date
 25-Feb-2014

 Print Date
 25-Feb-2014

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard