## **Safety Data Sheet**

Steps to Take in Case Material Is Released or Spilled:

Exposure to the spilled material may be severely irritating or toxic. Follow personal protective equipment recommendations found in Section 8 of this SDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits.

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Do not allow the spilled product to enter public drainage system or open waterways.

Sulfuric Acid, 3M Page 2 of 4

## **Safety Data Sheet**

**Conditions to Avoid:** Contact with water Reaction with water is exothermic.

Incompatible Materials: Water-reactive materials, Water, Organic Compounds, Strong reducing agents,

Acetaldehydes, Amines Sulfur containing gases

**Hazardous Decomposition Products:** 

Hazardous Polymerization:

Sulfuric Acid, 3M Page 3 of 4